



SIMATIC S7-1500 DIGITAL IN-/OUTPUT MODULE, DI16x 24VDC BA, 16 CHANNELS IN GROUPS OF 16, INPUT DELAY TYP. 3.2MS; INPUT TYPE 3 (IEC 61131), DQ 16X24VDC/0.5A BA; 16 CHANNELS IN GROUPS OF 8; 4A PER GROUP INCL. FRONT CONNECTOR PUSH-IN

General information	
Product type designation	DI 16x24VDC / DQ16x24VDC/0.5A BA
HW functional status	FS01
Firmware version	V1.0.0
• FW update possible	Yes
Product function	
• I&M data	Yes; I&M0 to I&M3
Engineering with	
• STEP 7 TIA Portal configurable/integrated as of version	V13 / V13
• STEP 7 configurable/integrated as of version	V5.5 SP3 / -
• PROFIBUS as of GSD version/GSD revision	V1.0 / V5.1
• PROFINET as of GSD version/GSD revision	V2.3 / -
Operating mode	
• DI	Yes
• Counter	No
• DQ	Yes
• DQ with energy-saving function	No
• PWM	No

• Oversampling • MSI • MSO	No Yes Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes; through internal protection with 7 A per group
Input current	
Current consumption, max.	30 mA
Output voltage	
Rated value (DC)	24 V
Power	
Power available from the backplane bus	1.1 W
Power loss	
Power loss, typ.	3.45 W
Digital inputs	
Number of digital inputs	16
Digital inputs, parameterizable	No
Source/sink input	P-reading
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Input voltage	
• Type of input voltage • Rated value (DC) • for signal "0" • for signal "1"	DC 24 V -30 to +5V +11 to +30V
Input current	
• for signal "1", typ.	2.7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	3 ms
— at "0" to "1", max.	4 ms
— at "1" to "0", min.	3 ms
— at "1" to "0", max.	4 ms
for interrupt inputs	
— parameterizable	No
Cable length	
• shielded, max.	1 000 m

- unshielded, max.

600 m

Digital outputs

Type of digital output	Transistor
Number of digital outputs	16
Current-sourcing	Yes
Short-circuit protection	Yes
• Response threshold, typ.	1 A
Limitation of inductive shutdown voltage to	L+ (-53 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
• with resistive load, max.	0.5 A
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	12 k Ω
Output voltage	
• for signal "1", min.	L+ (-0.8 V)
Output current	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, max.	0.5 A
• for signal "0" residual current, max.	0.5 mA
Output delay with resistive load	
• "0" to "1", max.	100 μ s
• "1" to "0", max.	500 μ s
Parallel switching of two outputs	
• for logic links	Yes
• for uprating	No
• for redundant control of a load	Yes
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	10 Hz
Total current of the outputs	
• Current per channel, max.	0.5 A; see additional description in the manual
• Current per group, max.	4 A; see additional description in the manual
• Current per module, max.	8 A; see additional description in the manual
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m

Encoder

Connectable encoders

• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA

Isochronous mode

Isochronous operation (application synchronized up to terminal)	No
---	----

Interrupts/diagnostics/status information

Diagnostics function	No
Substitute values connectable	No

Alarms

• Diagnostic alarm	No
• Hardware interrupt	No

Diagnostic messages

• Monitoring the supply voltage	No
• Wire-break	No
• Short-circuit	No
• Group error	No

Diagnostics indication LED

• RUN LED	Yes; Green LED
• ERROR LED	Yes; Red LED
• Monitoring of the supply voltage (PWR-LED)	Yes; Green LED
• Channel status display	Yes; Green LED
• for channel diagnostics	No
• for module diagnostics	No

Potential separation

Potential separation channels

• between the channels	No
• between the channels, in groups of	8
• between the channels and backplane bus	Yes

Isolation

Isolation tested with	707 V DC (type test)
-----------------------	----------------------

Ambient conditions

Ambient temperature during operation

• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	40 °C

Decentralized operation

Prioritized startup	Yes
---------------------	-----

Dimensions	
Width	25 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	280 g
Other	
Note:	Supplied incl. 40-pole push-in front connectors
last modified:	08/12/2017