



Figure similar

MLFB-Ordering data

6SL3121-2TE21-8AA3

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		Ambient conditions	
DC link voltage	DC 510 ... 720 V	Installation altitude (without derating)	1000 m (3281 ft)
Electronics power supply	DC 24 V -15 % / +20 %	Cooling ⁸⁾	External air cooling
Current demand, max.	1.00 A	Cooling air requirement	0.016 m ³ /s
DC-link current I _d	43.0 A	Ambient temperature	
Output current		During operation	0 ... 40 °C (32 ... 104 °F)
Rated value I _N	2 x 18.0 A	Connections	
Base load current I _H	2 x 15.3 A	Motor end	
For S6 duty (40%) I _{S6}	2 x 24.0 A	Version	connector (X1, X2)
I _{max}	2 x 36.0 A	PE connection	M5 screw
Type rating ²⁾		Shield connecting kit	Integrated connection plug (X1, X2)
Based on I _{IN}	2 x 9.7 kW	Max. motor cable length	
Based on I _H	2 x 8.2 kW	Shielded	70 m (230 ft)
Current carrying capacity		Unshielded	100 m (328 ft)
DC link busbars	100 A	Standards	
24 V busbars ⁴⁾	20 A	Compliance with standards	CE, cULus
DC link capacitance	705 μF	Safety Integrated	SIL 2 acc. to IEC 61508, PL d acc. to EN ISO 13849-1, Category 3 acc. to EN ISO 13849-1

MLFB-Ordering data

6SL3121-2TE21-8AA3



Figure similar

Mechanical data

Line side

Width	100.00 mm (3.94 in)
Height	380.00 mm (14.96 in)
Depth	226.00 mm (8.90 in)
Degree of protection	IP20
Type of construction	Booksize
Net weight	8.6 kg (18.96 lb)

General tech. specifications

Sound pressure level (1m)	60.0 dB
Power loss, max. ⁹⁾	0.24 kW

2) Rated output of a typical standard asynchronous motor at 400 V 3 AC

4) If, when connecting several Line Modules and Motor Modules in series, the current carrying capacity exceeds 20 A, another 24 V DC connection is required using a 24 V terminal adapter (max. connectable cross-section 6 mm², max. protection 20 A).

8) Power units with intensified air cooling thanks to integrated fan

9) Power loss of the Motor Module with rated power including losses of the 24 V DC electronics power supply